



Test Report

MERITEK ELECTRONICS CORPORATION
11824 HAMDEN PLACE
SANTA FE SPRINGS, CA 90670
USA

Report No. : CE/2004/93659B
Date : 2004/09/29
Page : 1 of 1

The following merchandise was (were) submitted and identified by the client as :

Type of Product : POLYMERIC POSITIVE TEMPERATURE COEFFICIENT
THERMISTOR(RESETTABLE FUSE)
Style/Item No : DIP TYPE / MPTR 90V SERIES
Sample Received : 2004/09/21
Testing Date : 2004/09/21 TO 2004/09/29

Test Result

PART NAME NO.1 : PLEASE REFER TO THE SAMPLE CARD(S). (MIX ALL PARTS)

Test Item (s):	Unit	Method	MDL	Result				
				No.1				
Chromium VI (Cr+6)	ppm	As per US EPA 7196A and US EPA 3060A.	2	N.D.				
Cadmium (Cd)	ppm	ICP-AES after as per EN 1122, method B:2001 or other acid digestion.	2	N.D.				
Mercury (Hg)	ppm	ICP-AES after as per US EPA 3052 or other acid digestion.	2	N.D.				
Lead (Pb)	ppm	ICP-AES after as per US EPA 3050B or other acid digestion.	2	86.9				

NOTE: (1) N.D. = Not detected (<MDL)
(2) ppm = mg/kg
(3) MDL = Method Detection Limit


Daniel Yeh, M.R. / Operation Manager
Signed for and on behalf of
SGS TAIWAN LTD.

The content of this PDF file is in accordance with the original issued reports for reference only. This Test Report cannot be reproduced, except in full, without prior written permission of the Company