











Conductive Polymer Capacitor SMT and Radial Type

Selection Guide

MERITEK

<u>Series</u>	<u>Load Life</u>	<u>Operating Temperature</u>	<u>Capacitance</u>	<u>Rated Voltage</u>	<u>Picture</u>
PECS	2000 Hours at 105°C	-55~105°C	220~330uF	2~2.5VDC	
PECH	2000 Hours at 105°C	-55~105°C	470uF	2~2.5VDC	
PEVA	2000 Hours at 105°C	-55~105°C	15~1000uF	2.5~25VDC	
PEV5	5000 Hours at 105°C	-55~105°C	22~820uF	2.5~25VDC	
PEEA	2000 Hours at 105°C	-55~105°C	27~560uF	2.5~25VDC	
PE	2000 Hours at 105°C	-55~105°C	270~2200uF	2.5~16VDC	
PEEP	3000 Hours at 105°C	-55~105°C	100~2200uF	6.3~20VDC	
PE5P	5000 Hours at 105°C	-55~105°C	270~1500uF	6.3~16VDC	
PE5K	5000 Hours at 105°C	-55~105°C	10~1000uF	2.5~25VDC	
PEHA	5000 Hours at 105°C	-55~105°C	47~1500uF	25~50VDC	

Conductive Polymer Capacitor series: http://www.meritekusa.com/EN/productlist/node/3_1286

Meritek product series: <http://www.meritekusa.com/EN/products>