


Transient Voltage Suppressors P600 Package

3KP Series

MERITEK

FEATURE

- Peak Pulse Power Dissipation: 3000W
- Fast response time. I_R less than $2\mu A$ above 10V
- Excellent clamping capability, Low incremental surge resistance
- Glass passivated junction
- High Temperature soldering guaranteed: 265°C, 10 seconds
- Terminals: Axial leads, solderable per MIL-STD-750, Method 2026
- UL Flammability Classification Rating 94V-0
- UL safety approved: certification No: E223045



MAXIMUM RATINGS AND CHARACTERISTICS


Parameter	Symbol	Value	Unit
Peak Pulse Power Dissipation on 10/1000 μs waveform. (Note 1, Fig. 1)	P_{PPM}	Minimum 3000	Watts
Peak Pulse Current on 10/1000 μs waveform. (Note 1, Fig. 3)	I_{PPM}	See Table	Amps
Steady State Power Dissipation at $T_L = 75^\circ C$, Lead length .375" (9.5mm). (Fig. 5)	$P_{M(AV)}$	7.0	Watts
Peak Forward Surge Current, 8.3ms Single Half Sine-wave Superimposed on Rated Load	I_{FSM}	300	Amps
Operating junction and Storage Temperature Range.	T_J, T_{STG}	-55 to +175	$^\circ C$

Ratings at 25°C ambient temperature unless otherwise specified.

1. Non-repetitive current pulse, per Fig. 3 and derated above $T_A = 25^\circ C$ per Fig. 2.
2. 8.3ms single half sine-wave, or equivalent square wave, Duty cycle = 4 pulses per minute maximum.

DIMENSIONS

Item	P600 (mm)	
	Min.	Max.
L	25.40	-
T	8.6	9.10
d	8.60	9.10
S	1.22	1.32



SPECIFICATIONS

Part Number		Reverse Stand-Off Voltage	Breakdown Voltage Min. @ I_T	Breakdown Voltage Max. @ I_T	Test Current	Maximum Clamping Voltage @ I_{PP}	Peak Pulse Current	Reverse Leakage @ V_{RWM}
Uni-Polar	Bi-Polar	$V_{RWM}(V)$	$V_{BR MIN.}(V)$	$V_{BR MAX.}(V)$	$I_T(mA)$	$V_C(V)$	$I_{PP}(A)$	$I_R(\mu A)$
3KP5.0A	3KP5.0CA	5.0	6.40	7.00	10	9.2	326.1	5000
3KP6.0A	3KP6.0CA	6.0	6.67	7.37	10	10.3	291.3	5000
3KP6.5A	3KP6.5CA	6.5	7.22	7.98	10	11.2	267.9	2000
3KP7.0A	3KP7.0CA	7.0	7.78	8.60	10	12.0	250.0	1000
3KP7.5A	3KP7.5CA	7.5	8.33	9.21	1	12.9	232.6	250
3KP8.0A	3KP8.0CA	8.0	8.89	9.83	1	13.6	220.6	150
3KP8.5A	3KP8.5CA	8.5	9.44	10.40	1	14.4	208.3	50
3KP9.0A	3KP9.0CA	9.0	10.00	11.10	1	15.4	194.8	20
3KP10A	3KP10CA	10.0	11.10	12.30	1	17.0	176.5	15
3KP11A	3KP11CA	11.0	12.20	13.50	1	18.2	164.8	2
3KP12A	3KP12CA	12.0	13.30	14.70	1	19.9	150.8	2
3KP13A	3KP13CA	13.0	14.40	15.90	1	21.5	139.5	2

Transient Voltage Suppressors P600 Package

3KP Series

MERITEK

SPECIFICATIONS (CONTINUED)

Part Number		Reverse Stand-Off Voltage	Breakdown Voltage Min.@I _T	Breakdown Voltage Max.@I _T	Test Current	Maximum Clamping Voltage @I _{PP}	Peak Pulse Current	Reverse Leakage @V _{RWM}
Uni-Polar	Bi-Polar	V _{RWM} (V)	V _{BR MIN.} (V)	V _{BR MAX.} (V)	I _T (mA)	V _C (V)	I _{PP} (A)	I _R (μA)
3KP14A	3KP14CA	14.0	15.60	17.20	1	23.2	129.3	2
3KP15A	3KP15CA	15.0	16.70	18.50	1	24.4	123.0	2
3KP16A	3KP16CA	16.0	17.80	19.70	1	26.0	115.4	2
3KP17A	3KP17CA	17.0	18.90	20.90	1	27.6	108.7	2
3KP18A	3KP18CA	18.0	20.00	22.10	1	29.2	102.7	2
3KP20A	3KP20CA	20.0	22.20	24.50	1	32.4	92.6	2
3KP22A	3KP22CA	22.0	24.40	26.90	1	35.5	84.5	2
3KP24A	3KP24CA	24.0	26.70	29.50	1	38.9	77.1	2
3KP26A	3KP26CA	26.0	28.90	31.90	1	42.1	71.3	2
3KP28A	3KP28CA	28.0	31.10	34.40	1	45.4	66.1	2
3KP30A	3KP30CA	30.0	33.30	36.80	1	48.4	62.0	2
3KP33A	3KP33CA	33.0	36.70	40.60	1	53.3	56.3	2
3KP36A	3KP36CA	36.0	40.00	44.20	1	58.1	51.6	2
3KP40A	3KP40CA	40.0	44.40	49.10	1	64.5	46.5	2
3KP43A	3KP43CA	43.0	47.80	52.80	1	69.4	43.2	2
3KP45A	3KP45CA	45.0	50.00	55.30	1	72.7	41.3	2
3KP48A	3KP48CA	48.0	53.30	58.90	1	77.4	38.8	2
3KP51A	3KP51CA	51.0	56.70	62.70	1	82.4	36.4	2
3KP54A	3KP54CA	54.0	60.00	66.30	1	87.1	34.4	2
3KP58A	3KP58CA	58.0	64.40	71.20	1	93.6	32.1	2
3KP60A	3KP60CA	60.0	66.70	73.70	1	96.8	31.0	2
3KP64A	3KP64CA	64.0	71.10	78.60	1	103.0	29.1	2
3KP70A	3KP70CA	70.0	77.80	92.10	1	113.0	26.5	2
3KP75A	3KP75CA	75.0	83.30	92.10	1	121.0	24.8	2
3KP78A	3KP78CA	78.0	86.70	95.80	1	126.0	23.8	2
3KP85A	3KP85CA	85.0	94.40	104.00	1	137.0	21.9	2
3KP90A	3KP90CA	90.0	100.00	111.00	1	146.0	20.5	2
3KP100A	3KP100CA	100.0	111.00	123.00	1	162.0	18.5	2
3KP110A	3KP110CA	110.0	122.00	135.00	1	177.0	16.9	2
3KP120A	3KP120CA	120.0	133.00	147.00	1	193.0	15.5	2
3KP130A	3KP130CA	130.0	144.00	159.00	1	209.0	14.4	2
3KP150A	3KP150CA	150.0	167.00	185.00	1	243.0	12.3	2
3KP160A	3KP160CA	160.0	178.00	197.00	1	259.0	11.6	2
3KP170A	3KP170CA	170.0	189.00	209.00	1	275.0	10.9	2
3KP180A	3KP180CA	180.0	201.00	222.00	1	292.0	10.4	2
3KP190A	3KP190CA	190.0	211.00	233.20	1	308.0	9.7	2
3KP200A	3KP200CA	200.0	224.00	247.00	1	324.0	9.3	2
3KP210A	3KP210CA	210.0	237.00	263.00	1	340.0	8.8	2
3KP220A	3KP220CA	220.0	246.00	272.00	1	356.0	8.4	2


Transient Voltage Suppressors P600 Package

3KP Series


MERITEK

CHARACTERISTIC CURVES


Peak Pulse Power Rating Curve




Pulse Derating Curve




Pulse Waveform




Typical Junction Capacitance



Steady State Power Dissipation Derating Curve



Maximum Non-Repetitive Forward Surge Current Uni-Directional Only






Transient Voltage Suppressors P600 Package

3KP Series

MERITEK


PACKAGING SPECIFICATION

Tape	
Symbol	Dimension(mm)
A	10.0±0.5
B	53.0±1.0
Z	1.2Max.
T	6.0±0.4
E	0.8Max.
L1-L2	1.0Max.
Box	
Symbol	Dimension(mm)
L	250.0±5.0
W	75.0±5.0
H	114.0±5.0
Quantity: 300PCS	
Reel	
Symbol	Dimension(mm)
D	330.0±3.0
D0	16.4±2.0
D1	86.0±2.0
W1	76.0±3.0
Quantity: 800PCS	



WAVE SOLDERING RECOMMENDATION

Item	Conditions
Peak Temperature	265°C
Dipping Time	10 Seconds
Soldering	1 time



*Specifications subject to change without notice.