

ESD Suppressor


5V 2-Unidirectional SOT-23

ME52U11V2S23

MERITEK


FEATURE

- IEC 61000-4-2 ESD: $\pm 15\text{KV}$ (Air) $\pm 8\text{KV}$ (Contact)
- ESD Protection for two Unidirectional Channels
- ESD Protection for one Bidirectional Channel
- Low Clamping Voltage



APPLICATION

- Industrial Controls
- Set-Top Box
- Portable Devices
- Notebooks, PC Desktops and Servers



MAXIMUM RATINGS AND CHARACTERISTICS

Parameter	Symbol	Value	Unit
ESD Voltage (Contact discharge)	V_{ESD}	± 8	KV
ESD Voltage (Air discharge)		± 15	
Peak Pulse Power ($t_p=8/20\mu\text{s}$)	P_{PP}	140	W
Peak Pulse Current ($t_p=8/20\mu\text{s}$)	I_{PP}	13	A
Operating & Storage Temperature Range	T_J, T_{STG}	$-50 \sim +150$	$^{\circ}\text{C}$

ELECTRICAL CHARACTERISTICS

Parameter	Condition	Symbol	Min.	Typ.	Max.	Unit
Reverse Stand-Off Voltage	--	V_{RWM}	--	--	5	V
Reverse Breakdown Voltage	$I_{\text{BR}}=1\text{mA}$	V_{BR}	6	--	--	V
Reverse Leakage Current	$V_{\text{RWM}}=5\text{V}$	I_{R}	--	--	20	μA
Forward Voltage	$I_{\text{F}}=100\text{mA}$, 300 μs -square wave	V_{F}	--	--	1.5	V
Clamping Voltage	$I_{\text{PP}}=13\text{A}$, $t_p=8/20\mu\text{s}$	V_{C}	--	--	11.2	V
Off State Junction Capacitance	$V_{\text{dc}}=0$, $f=1\text{MHz}$, Between I/O pins and GND	C_{J}	--	--	120	pF

Notes:

1. $T_A=25^{\circ}\text{C}$ unless otherwise specified


ESD Suppressor 5V 2-Unidirectional SOT-23

ME52U11V2S23


MERITEK

CHARACTERISTIC CURVES


Typical Capacitance vs. Reverse Voltage



Typical Clamping Voltage



Typical Leakage Current vs. Junction Temperature



ESD Suppressor





5V 2-Unidirectional SOT-23

ME52U11V2S23

MERITEK

DIMENSIONS AND RECOMMENDED LAND PATTERN

Item	Min (mm)	Max (mm)
A1	0.08	0.20
A2	0.82	0.90
b	0.35	0.50
C	0.00	0.10
D	2.80	3.04
e	--	--
e1	1.80	2.00
E	2.20	2.60
E1	1.20	1.40
L	0.15	--
X	0.80	0.80
X1	1.35	1.35
Y	2.90	2.90
Y1	0.90	0.90
Y2	2.00	2.00



*Specifications subject to change without notice.