

Aluminum Electrolytic Capacitors

Surface Mount AEC-Q200

SHL-A series

MERITEK

FEATURE

- Low Leakage Current Series
- AEC-Q200 Compliant
- Load Life at 105°C

Diameter (mm)	Load Life (Hours)
4.0 ~ 6.3	2000



SPECIFICATIONS



Item	Characteristic										
Operating Temperature	-40 ~ 105°C										
Rated Working Voltage	6.3 ~ 50VDC										
Nominal Capacitance	1 ~ 100µF, ±20% (at 20°C, 120HZ)										
Leakage Current	Frequency (Hz)	60	120	1K	10K	--	--				
	Coefficient	0.85	1.00	1.10	1.20	--	--				
	Dissipation Factor	0.24	0.20	0.16	0.14	0.12	0.10				
	Working Voltage (V)	6.3	10	16	25	35	50				
Dissipation Factor at 20°C, 120Hz	Z-25°C / Z+20°C	4	3	2	2	2	2				
	Z-40°C / Z+20°C	8	6	4	4	3	3				
Load Life	Capacitance	≤ ±25% of initial value		Apply Working Voltage for Rated Load Life / Temperature Stabilized at +20°C.							
	Dissipation Factor	≤ 200% of initial value									
	Leakage Current	≤ Initial specified value									
Shelf Life	Capacitance	≤ ±25% of initial value		After storage condition without voltage applied for 1000 hours at Rated Temperature, Stabilizing for 1 to 2 hours.							
	Dissipation Factor	≤ 200% of initial value									
	Leakage Current	≤ Initial specified value									
Resistance to Soldering Heat	Capacitance	≤ ±20% of initial value		For other procedures than those specified, Soldering iron method: Temperature: 260±5°C. Application time of soldering iron: 10 sec							
	Dissipation Factor	≤ specified value									
	Leakage Current	≤ specified value									

Aluminum Electrolytic Capacitors

Surface Mount AEC-Q200

SHL-A series

MERITEK


STANDARD RATING

Rated Voltage	Rated Capacitance		Case Size	Tan δ	Ripple Current
(V _{DC})	(μF)	Code	(mm)	(%)	(mA/rms)
6.3	22	220	4x5.4	0.24	24
	33	330	5x5.4	0.24	33
	47	470	5x5.4	0.24	39
	100	101	6.3x5.4	0.24	65
10	22	220	5x5.4	0.20	30
	33	33	5x5.4	0.20	36
	47	470	6.3x5.4	0.20	50
	100	101	6.3x5.4	0.20	70
16	10	100	4x5.4	0.16	20
	22	220	5x5.4	0.16	33
	33	330	6.3x5.4	0.16	46
	47	470	6.3x5.4	0.16	55

Note: Ripple Current measured at 120Hz, 105°C

Rated Voltage	Rated Capacitance		Case Size	Tan δ	Ripple Current
(V _{DC})	(μF)	Code	(mm)	(%)	(mA/rms)
25	4.7	4R7	4x5.4	0.14	14
	10	100	5x5.4	0.14	24
	22	220	6.3x5.4	0.14	41
	33	330	6.3x5.4	0.14	50
35	4.7	4R7	4x5.4	0.12	15
	10	100	5x5.4	0.12	26
	22	220	6.3x5.4	0.12	44
	1.0	1R0	4x5.4	0.10	8
50	2.2	2R2	4x5.4	0.10	12
	3.3	3R3	4x5.4	0.10	14
	4.7	4R7	5x5.4	0.10	19
	10	100	6.3x5.4	0.10	32

DIMENSION



Unit: mm

D	L	A ±0.2	B ±0.2	H Max	W ±0.1	P ±0.2	K
4.0 (D)	5.4	4.3	5.0	5.5	0.65	1.0	0.35+0.15/-0.2
5.0 (E)	5.4	5.3	6.0	6.5	0.65	1.5	0.35+0.15/-0.2
6.3 (F)	5.4	6.6	7.3	7.8	0.65	2.1	0.35+0.15/-0.2

Aluminum Electrolytic Capacitors

Surface Mount AEC-Q200

SHL-A series

MERITEK

PART NUMBERING SYSTEM

SHL 1H 100 A F054

(1) (2) (3) (4) (5)

No	Item	Code	Description					
(1)	Product Code	SHL	Aluminum Electrolytic Capacitors, SMD type, 2000 Hrs 105°C					
(2)	Rated Voltage	1H	50VDC		DC Voltage Code			
(3)	Capacitance	100	10µF ±20% (M)		First two digits: significant, Third: Multiplier			
(4)	Series Code	A	AEC-Q200 Compliant Series					
(5)	Size Code	F054	6.3x5.4mm		DxL (mm)			

Voltage	4	6.3	10	16	25	35	50	63	100	160	200	250	350	400	450	500
Code	0G	0J	1A	1C	1E	1V	1H	1J	2A	2C	2D	2E	2V	2G	2W	2H

Diameter	4	5	6.3	8	10	12.5	14.5	16	18	20	22	25
Code	D	E	F	H	J	K	U	L	M	N	P	Q

*Specifications subject to change without notice.