

Common Mode Filter 3.2x2.5mm

SIC10-41 series

MERITEK

FEATURE

- Common Mode Filter For Large Current Applications
- Excellent Impedance Characteristics for Noise Suppression
- Low Profile Construction Design
- Application: High-Density Portable Devices, Personal Computers, Display Panels, DC Power Lines and Automotive Power Trains




ELECTRICAL CHARACTERISTICS

| Part Number | Common Mode Impedance (Ω) | Test Frequency (MHz) | DCR Max (m Ω) | Rated Current (mA) | Rated Voltage (Vdc) | IR Min (M Ω) | Withstand Voltage (Vdc) |
|---------------|------------------------------------|----------------------|-----------------------|--------------------|---------------------|----------------------|-------------------------|
| SIC109001A041 | 90 \pm 25% | 100 | 50 | 1000 | 50 | 10 | 125 |
| SIC106011A041 | 600 \pm 25% | 100 | 200 | 1000 | 50 | 10 | 125 |
| SIC10102A4041 | 1000 \pm 25% | 100 | 300 | 400 | 50 | 10 | 125 |

Notes:

1. All test data referenced to 25°C ambient.
2. Operating Temperature: -40°C ~ +105°C (Including Self-temperature rise)

DIMENSIONS



Unit: mm

| Size Code | A \pm 0.2 | B \pm 0.2 | C \pm 0.2 | D \pm 0.1 | D1 \pm 0.1 | E Typ | X | Y | G1 | G2 |
|-----------|-------------|-------------|-------------|-------------|--------------|-------|-----|-----|-----|-----|
| 10 (1210) | 3.2 | 2.50 | 2.2 | 0.80 | 0.90 | 1.4 | 4.4 | 3.5 | 1.6 | 0.6 |

PART NUMBERING SYSTEM

SIC 10 102 A40 41
(1) (2) (3) (4) (5)




| No | Item | Code | Description |
|-----|----------------|------|--|
| (1) | Product Code | SIC | Surface Mount Inductor, Common Mode Choke type |
| (2) | Dimension Code | 10 | 10: 1210 3.2 X 2.5mm, L x W (mm) |
| (3) | Impedance | 102 | 1000 Ω First two digits: significant, Third: Multiplier |
| (4) | Rated Current | A40 | 0.4A A: Decimal |
| (5) | Series Code | 41 | Common Mode Filter, for Power Line |

Common Mode Filter 3.2x2.5mm


SIC10-41 series

MERITEK

CHARACTERISTIC CURVE




DIMENSIONS – SIC-41 Series



Unit: mm

| Size Code | A ±0.2 | B ±0.2 | C ±0.2 | D ±0.1 | D1 ±0.1 | E Typ | X | Y | G1 | G2 |
|-----------|--------|--------|--------|--------|---------|-------|-----|------|-----|------|
| 04 (0504) | 1.2 | 1.00 | 0.9 | 0.35 | 0.35 | 0.5 | 1.5 | 1.2 | 0.6 | 0.3 |
| 03 (0603) | 1.6 | 0.85 | 1.1 | 0.30 | 0.30 | 1.0 | 2.3 | 0.75 | 0.6 | 0.25 |
| 05 (0805) | 2.0 | 1.20 | 1.2 | 0.50 | 0.50 | 1.0 | 2.6 | 1.25 | 1.1 | 0.45 |
| 06 (1206) | 3.2 | 1.60 | 2.0 | 0.50 | 0.50 | 2.2 | 3.7 | 1.6 | 1.9 | 0.4 |
| 10 (1210) | 3.2 | 2.50 | 2.2 | 0.80 | 0.90 | 1.4 | 4.4 | 3.5 | 1.6 | 0.6 |
| 12 (1812) | 4.5 | 3.20 | 2.8 | 1.00 | 1.20 | 2.1 | 4.8 | 3.8 | 2.5 | 0.7 |



Unit: mm

| Size Code | A ±0.5 | B ±0.5 | C Max | D | D1 | E Typ | X | Y | G1 | G2 |
|-----------|--------|--------|-------|----------|----------|-------|------|-----|-----|-----|
| 121 | 12 | 10.8 | 6.4 | 2.7 ±0.2 | 2.5 ±0.2 | 7.0 | 12.2 | 8.1 | 6.8 | 2.3 |
| 70F | 7.0 | 6.00 | 3.8 | 1.5 ±0.5 | 1.7 ±0.5 | 3.5 | 9.0 | 4.5 | 4.0 | 1.5 |
| 70C | 7.0 | 6.00 | 3.8 | 1.5 Typ | 1.7 Typ | 3.5 | 9.0 | 4.5 | 4.0 | 1.5 |
| 907 | 9.0 | 7.00 | 4.8 | 1.5 ±0.2 | 1.7 ±0.2 | 5.7 | 11 | 5.0 | 5.0 | 1.5 |



Common Mode Filter

3.2x2.5mm

SIC10-41 series

MERITEK

RELIABILITY TEST CONDITON AND REQUIREMENT

| Item | Test Standards / Conditions / Equipment | Requirement | | | | | | | | | | | | | | | |
|--|--|---|--------------------------|--------------------------|-----------------------------|-----------------------------|-----|----|----|-----------|------|------|----|----|-----------|------|---|
| Impedance | Agilent-4291A, Agilent-16197A | Refer to specification | | | | | | | | | | | | | | | |
| DC Resistance | Agilent-4338B | Refer to specification | | | | | | | | | | | | | | | |
| I.R | Agilent-4339 | Refer to specification | | | | | | | | | | | | | | | |
| Temperature Rise Test | 1. Applied the allowed DC current 2. Temperature measured by digital surface thermometer | Rated Current < 1A : $\Delta T = 20^{\circ}\text{C}$ Max Rated Current $\geq 1\text{A}$: $\Delta T = 40^{\circ}\text{C}$ Max | | | | | | | | | | | | | | | |
| Mechanical Shock | <table border="1"> <thead> <tr> <th>Type</th> <th>Peak value (g's)</th> <th>Normal duration (D) (ms)</th> <th>Wave form</th> <th>Velocity change (Vi) ft/sec</th> </tr> </thead> <tbody> <tr> <td>SMD</td> <td>50</td> <td>11</td> <td>Half-sine</td> <td>11.3</td> </tr> <tr> <td>Lead</td> <td>50</td> <td>11</td> <td>Half-sine</td> <td>11.3</td> </tr> </tbody> </table> | Type | Peak value (g's) | Normal duration (D) (ms) | Wave form | Velocity change (Vi) ft/sec | SMD | 50 | 11 | Half-sine | 11.3 | Lead | 50 | 11 | Half-sine | 11.3 | Appearance: No damage Impedance: within $\pm 15\%$ of initial value Inductance: within $\pm 10\%$ of initial value Q: Shall not exceed the specification value RDC: within $\pm 15\%$ of initial value and shall not exceed the specification value |
| | Type | Peak value (g's) | Normal duration (D) (ms) | Wave form | Velocity change (Vi) ft/sec | | | | | | | | | | | | |
| SMD | 50 | 11 | Half-sine | 11.3 | | | | | | | | | | | | | |
| Lead | 50 | 11 | Half-sine | 11.3 | | | | | | | | | | | | | |
| 3 shocks in each direction along 3 perpendicular axes (18 shocks). | | | | | | | | | | | | | | | | | |
| Solderability | Method B1, 4 Hrs at 155°C dry heat at $255^{\circ}\text{C} \pm 5^{\circ}\text{C}$ Test Time: 5 +0/-0.5 seconds. Method D category 3. (steam aging 8 hours $\pm 15\text{min}$) at $260^{\circ}\text{C} \pm 5^{\circ}\text{C}$ Test Time: 30+0/-0.5 seconds. | More than 95% of the terminal electrode should be covered with solder. | | | | | | | | | | | | | | | |
| Resistance to Soldering Heat | Solder temperature: $260 \pm 5^{\circ}\text{C}$ for 10 seconds Temperature ramp/immersion and emersion rate $25\text{mm/s} \pm 6\text{ mm/s}$. Completely cover the termination. Number of cycles: 1 heat cycle | Appearance: No damage Impedance: within $\pm 15\%$ of initial value Inductance: within $\pm 10\%$ of initial value Q: Shall not exceed the specification value RDC: within $\pm 15\%$ of initial value and shall not exceed the specification value | | | | | | | | | | | | | | | |
| Vibration | Oscillation Frequency: $10 \sim 2\text{K} \sim 10\text{ Hz}$ for 20 minutes Total Amplitude: $1.52\text{mm} \pm 10\%$ Testing Time: 12 hours (20 minutes, 12 cycles each of 3 orientations) | | | | | | | | | | | | | | | | |
| Load Humidity | Humidity: $85 \pm 2\%$ R.H. Temperature: $85^{\circ}\text{C} \pm 2^{\circ}\text{C}$ Duration: 1000Hrs Min at 100% rated current Measured at Room Temperature after $24 \pm 2\text{hrs}$ | Appearance: No damage Impedance: within $\pm 15\%$ of initial value Inductance: within $\pm 10\%$ of initial value Q: Shall not exceed the specification value RDC: within $\pm 15\%$ of initial value and shall not exceed the specification value | | | | | | | | | | | | | | | |
| Life Test | Temperature: $125 \pm 2^{\circ}\text{C}$ Duration: 1000Hrs Min. with 100% rated current Measured at Room Temperature after $24 \pm 2\text{Hrs}$ | | | | | | | | | | | | | | | | |
| Thermal Shock | Temperature: $-40 \sim 125^{\circ}\text{C}$ Dwell Time: 15minutes, Transfer Time: 20seconds Max Number of Cycles: 300cycles Measured at room temperature after placing for $24 \pm 2\text{hrs}$ | | | | | | | | | | | | | | | | |
| Terminal Strength | Component mounted on a PCB apply a force to the side of a device being tested. $> 0.805\text{inch}$ (2012mm): 1Kg, $\leq 0.805\text{inch}$ (2012mm): 0.5Kg Duration 60 +1 seconds. The force shall be applied gradually as not to shock the component being tested. |  Appearance : No damage | | | | | | | | | | | | | | | |
| Board Flex | Place the $100 \times 40\text{mm}$ FR4 board into a fixture with the component facing down. Apply a force which will bend the board: $\geq 0.805\text{in}$ (2012mm): 1.2mm $< 0.805\text{in}$ (2012mm): 0.8mm Duration: 10 seconds. The Force is to be applied only once to the board |  Appearance : No damage | | | | | | | | | | | | | | | |
| Moisture Resistance | 1. Baked at 50°C for 25hrs, measure at room temp after 4hrs. 2. Raise temperature to $65 \pm 2^{\circ}\text{C}$ 90-100%RH in 2.5hrs, 3. Keep at 65°C for 3 hours, cool down to 25°C in 2.5hrs. 4. Raise temperature to $65 \pm 2^{\circ}\text{C}$ 90-100%RH in 2.5hrs 5. Keep at 65°C for 3hrs, cool down to 25°C in 2.5hrs 6. Keep at 25°C for 2hrs then keep at -10°C for 3hrs 7. Keep at 25°C 80-100%RH for 15min, Vibrate at the frequency of 10 to 55 Hz to 10 Hz, Measure at room temperature after 1~2 hrs. | Appearance: No damage Impedance: within $\pm 15\%$ of initial value Inductance: within $\pm 10\%$ of initial value Q: Shall not exceed the specification value RDC: within $\pm 15\%$ of initial value and shall not exceed the specification value | | | | | | | | | | | | | | | |

Common Mode Filter 3.2x2.5mm

SIC10-41 series

MERITEK

RECOMMENDED SOLDERING PROFILES

| Reflow Condition | | |
|---|-------------------------------|------------------|
| Pre Heat | Temp. Min $T_{s(min)}$ | 150°C |
| | Temp. Max $T_{s(max)}$ | 200°C |
| | Time (min. to max.) (t_s) | 60 ~ 120 seconds |
| Average ramp up rate (Liquidus Temperature) (T_L) to peak | | 3°C/second max |
| $T_{s(max)}$ to T_L (Ramp-up rate) | | 3°C/second max |
| Reflow | Temp. (T_L) | 217°C |
| | Time (min. to max.) (t_L) | 60 ~ 150 seconds |
| Peak Temperature (T_P) | | See table below |
| Time within 5°C of actual peak Temperature (t_p) | | 10 seconds max |
| Ramp-down Rate | | 6°C/second max |
| Reflow Times | | 3 times max |

| Peak Temperature (T_P) | | | |
|----------------------------|----------------------|-------------------------|-----------------------|
| Volume | < 350mm ³ | 350-2000mm ³ | > 2000mm ³ |
| Thickness < 1.6mm | 260°C | 260°C | 260°C |
| Thickness 1.6-2.5mm | 260°C | 250°C | 245°C |
| Thickness ≥ 2.5mm | 250°C | 245°C | 245°C |

*Specifications subject to change without notice

