


Fast Recovery Rectifier 1200V 60A TO-247-2

FRED60120T2472

MERITEK


FEATURES

- Optimized Performance Between V_F & T_R
- Soft Recovery Characteristic
- Reduced EMI and Improved Performance
- Improved Thermal Performance
- Application: Rectifiers in Switching Mode Power, UPS, PV Inverter, EV Charging Station, and Welder



MECHANICAL DATA

- Case: TO-247-2, Molded Plastic
- Terminals: Solderable per MIL-STD-750, Method 2026



MAXIMUM RATINGS

Parameter	Symbol	Value	Units
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	1200	V
Maximum DC Blocking Voltage	V_{DC}	1200	
Average Forward Rectified Current at $T_L=105^\circ\text{C}$	$I_{F(AV)}$	60	A
Repetitive Peak Surge Current, 8.3ms, Sine-Wave, D=0.5	I_{FRM}	120	
Peak Forward Surge Current, 8.3ms Single Half-Sine-Wave Superimposed on Rated Load	I_{FSM}	330	
Maximum Power Dissipation	P_{TOT}	313	W
Maximum Thermal Resistance	$R_{\theta JC}$	0.4	$^\circ\text{C/W}$
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55~+150	$^\circ\text{C}$


ELECTRICAL CHARACTERISTICS

Parameter	Conditions	Symbol	Min	Typ.	Max	Unit
Instantaneous Forward Voltage	$I_F=60\text{A}, T_J=25^\circ\text{C}$	V_F	--	2.0	2.5	V
	$I_F=60\text{A}, T_J=125^\circ\text{C}$		--	1.8	--	
Reverse Leakage Current	$V_R=1200\text{V}, T_J=25^\circ\text{C}$	I_R	--	--	250	μA
	$V_R=1200\text{V}, T_J=125^\circ\text{C}$		--	--	1	mA
Maximum Reverse Recovery Time $T_J=25^\circ\text{C}$	$I_F=0.5\text{A}, I_R=1\text{A}, I_{RR}=0.25\text{A}$	T_{RR}	--	--	70	nS
	$I_F=1\text{A}, V_R=30\text{V}, di/dt=300\text{A}/\mu\text{s}$		--	--	50	
Reverse Recovery Time	$I_F=60\text{A}, V_R=400\text{V}, di/dt=300\text{A}/\mu\text{s}, T_J=25^\circ\text{C}$	T_{RR}	--	220	330	nS
Peak Recovery Current		I_{RRM}	--	10.5	--	A
Reverse Recovery Charge		Q_{RR}	--	1250	--	nC
Softness factor = t_b/t_a		S	--	2.6	--	--
Reverse Recovery Time	$I_F=60\text{A}, V_R=400\text{V}, di/dt=300\text{A}/\mu\text{s}, T_J=125^\circ\text{C}$	T_{RR}	--	385	--	nS
Peak Recovery Current		I_{RRM}	--	24	--	A
Reverse Recovery Charge		Q_{RR}	--	4700	--	nC
Softness factor = t_b/t_a		S	--	2.0	--	--


Notes: $T_C=25^\circ\text{C}$ unless otherwise noted

CHARACTERISTIC CURVES


Forward Current Derating Curve




Typical Junction Capacitance




Typical Reverse Characteristics




Typical Forward Characteristics



Typical Reverse Recovery Time



Typical Reverse Recovery Charge



Fast Recovery Rectifier
1200V 60A TO-247-2

FRED60120T2472

MERITEK

DIMENSIONS

Item	Min (mm)	Max (mm)
A	4.83	5.21
A1	2.29	2.55
A2	1.50	2.49
b	1.12	1.33
b2	1.91	2.39
c	0.50	0.69
D	20.80	21.30
D1	16.25	17.65
D2	0.51	1.35
E	15.73	16.13
E1	13.46	14.16
E2	4.32	5.49
e1	10.88 BSC	
L	19.75	20.32
L1	3.70	4.40
p	3.56	3.65
p1	7.15 REF	
Q	6.04	6.30
S	5.39	6.20

Notes: Pin 1: Cathode; Pin 3: Anode

